

CW3002H/3003H/04/06

吹膜、印刷复合通用电晕机

CW3002H/3003H/04/06 CORONA TREATMENT FOR FILM BLOWING/PRINTING MACHINE



CW3002H/3003H



CW3004/3006

主要特点

- ◆ 采用挂式结构，安置方便(CW3002H)
- ◆ 主回路逆变部分采用进口IGBT功率模块及专用驱动电路
- ◆ 固定电路工作频率，调节脉冲宽度而改变输出功率
- ◆ 具有软启动功能，防止大电流对电网的污染及对设备的损害
- ◆ 具有胶辊停转保护功能

Main Characteristics

- ◆ It adopts hang fabric, convenience to setting.(CW3002H)
- ◆ It adopts the imported driver circuit and power organ IGBT in the main loop
- ◆ Fixedness operating frequency, you can adjust the width of pulse to change the output power.
- ◆ It has the function of soft-start, which can reduce the pollution to the net and protect the equipment.
- ◆ It has stop-running protection to protect the rubber-roller.

技术规格 Technical Specification	CW3002H	CW3003H	CW3004	CW3006
输入电压、频率 Input Voltage and Frequency	AC220V 50Hz	AC220V 50Hz	AC380V 50Hz	AC380V 50Hz
输出电压(Max) Output Voltage (Max)	15KV	15KV	15KV	15KV
输出功率(Max) Output Opwer (Max)	2KW	3KW	4KW	6KW
工作频率 Operating Frequency	19KHz	19KHz	19KHz	19KHz
外形尺寸(控制箱)(mm) Size of Control Cabinet (mm)	475 × 180 × 325	475 × 180 × 325	300 × 380 × 800	300 × 380 × 800
变压器箱(mm) Size of Transformer Box (mm)	-	-	300 × 350 × 300	300 × 350 × 300
重量(控制箱+变压器箱)(Kg) Weight (Control Cabinet + Transformer Box)	12	12	55	60

南通三信塑胶装备科技股份有限公司

公司地址：江苏省启东市台角工业区
 网址：www.ntsaxin.com www.ntsaxin.cn
 总机：0513-83214154 传真：0513-83214152
 邮箱：ntsax@ntsaxin.com

NANTONG SANXIN PLASTICS EQUIPMENT TECHNOLOGY CO.,LTD

Address:Taijiao Industrial Zone, Qidong City, Jiangsu Province, China

Website: www.ntsaxin.com www.ntsaxin.cn

Tel: 0086-513-83214154 Fax: 0086-513-83214152 Email: ntsx@ntsaxin.com

CW1000

吹膜、印刷复合通用电晕机

CW1000 CORONA TREATMENT



CW1001H2/1002



CW1002/CW1003

主要特点

- ◆ 采用GTR管作为功率转换器件
- ◆ 超高效能，高频输出（8-25KHz）
- ◆ 输出功率连续可调
- ◆ 全电子保护、低速度自停
- ◆ 适用于制膜、印刷、涂胶、复合机组

Main Characteristics

- ◆ Take GTR as the power switch organ
- ◆ High efficiency, high operating frequency(8-25KHz)
- ◆ Power output is continuous adjustable
- ◆ Electronic protection and automatic stopping
- ◆ Server in the film production, publishing, gelatinization, and complex unit.

型号 Type	CW1001	CW1002	CW1003
供电电压 Power Supply	220V	220V	220V
工作频率Khz Operation Frequency	8-25	8-25	8-25
最大输出功率Kw The Max Output Power	1	2	3
最大处理宽度mm The Max Treating Width	650	1000	1200
适用范围 Treating Material	PP, PE, PS etc.		

南通三信塑胶装备科技股份有限公司

公司地址：江苏省启东市台角工业区
 网址：www.ntsaxin.com www.ntsaxin.cn
 总机：0513-83214154 传真：0513-83214152
 邮箱：ntsax@ntsaxin.com

NANTONG SANXIN PLASTICS EQUIPMENT TECHNOLOGY CO.,LTD

Address: Taijiao Industrial Zone, Qidong City, Jiangsu Province, China
 Website: www.ntsaxin.com www.ntsaxin.cn
 Tel: 0086-513-83214154 Fax: 0086-513-83214152 Email: ntsax@ntsaxin.com