

# CW3008/10/15

## 吹膜、印刷复合通用电晕机

### CW3008/10/15 CORONA TREATMENT FOR FILM BLOWING/PRINTING MACHINE



CW3008



CW3010/3015

## 主要特点

- ◆ 采用IGBT功率转换器件可靠性高
- ◆ 工作频率自动跟踪、锁定
- ◆ 轻载启动装置，减少对电网污染
- ◆ 具有输入缺相、错相、过电压，输出过流短路及跳火保护功能
- ◆ 具有胶辊停转及电极架开启保护功能，极大的减少胶辊被击穿的可能性

## Main Characteristics

- ◆ It adopts power switching IGBT module, and is high reliability.
- ◆ It tracks and locks the operating frequency automatically.
- ◆ It has the function of low load start, which can eliminate the interference to the power supply and electronic equipment.(Except CW3002H).
- ◆ It has kinds of protection such as phase absence, phases error, over voltage and short circuit protection.
- ◆ It has protection function for the rubber roller stop-running and electrode opening.

技术规格 Technical Specification	CW3008	CW3010/3015
输入电压、频率 Input Voltage and Frequency	三相 380V ± 10% 50Hz	三相 380V ± 10% 50Hz
输出电压(Max) Output Voltage (Max)	15KV	15KV
输出功率(Max) Output Opwer (Max)	8KW	10KW/15KW
工作频率 Operating Frequency	15-40KHz	15-40KHz
外形尺寸(控制箱)(mm) Size of Control Cabinet (mm)	460 × 300 × 960	600 × 600 × 1500
变压器箱(mm) Size of Transformer Box (mm)	300 × 350 × 300	460 × 320 × 360
重量(控制箱+变压器箱)(Kg) Weight (Control Cabinet + Transformer Box)	75	135

## 南通三信塑胶装备科技股份有限公司

公司地址：江苏省启东市台角工业区  
 网址：www.ntsaxin.com www.ntsaxin.cn  
 总机：0513-83214154 传真：0513-83214152  
 邮箱：ntsx@ntsaxin.com

## NANTONG SANXIN PLASTICS EQUIPMENT TECHNOLOGY CO.,LTD

Address:Taijiao Industrial Zone, Qidong City, Jiangsu Province, China  
 Website: www.ntsaxin.com www.ntsaxin.cn  
 Tel: 0086-513-83214154 Fax: 0086-513-83214152 Email: ntsx@ntsaxin.com

# CW3020/30/60

## 大功率电晕处理机

### CW3020/30/60 HIGH-POWER CORONA TREATMENT



CW3020/3030



CW3060

## 主要特点

- ◆ 采用IGBT功率转器件可靠性高
- ◆ 工作频率自动跟踪、锁定
- ◆ 轻载启动装置，减少对电网污染
- ◆ 具有记忆功能，重新启动后输出功率自动稳定在上次设定值，同时在启动之前可重新设定输出功率大小。（仅计算机控制的机型）
- ◆ 具有输入缺相、错相、过电压，输出短路及跳火保护功能
- ◆ 具有胶辊停转及电极架开启保护功能，极大的减少胶辊被击穿的可能性
- ◆ 数字操作面板可显示输入电压、输入电流、输入功率、直流电压、直流电流、有功功率、工作频率等参数。（仅计算机控制的机型）

## Main Characteristics

- ◆ It adopts power switching IGBT module, and is high reliability. It tracks and locks the operating frequency automatically.
- ◆ It has the function of soft-start, which can eliminate the interference to the power supply.
- ◆ It has memory. When the machine restart, the output power is steady at the value you set last time. You can also set the power value before the restart.(only computer controllable type)
- ◆ It has kinds of protection such as phase absence, phases error, over voltage and short circuit.
- ◆ It has protection function for the rubber roller stop-running and electrode opening.
- ◆ The digital operating panel can show the values of input voltage, input current, input power, dc-voltage,avail power, operating frequency.(only computer controllable type)

技术规格 Technical Specification	CW3020	CW3030	CW3060
输入电压、频率 Input Voltage and Frequency	三相 380V ± 10% 50Hz	三相 380V ± 10% 50Hz	三相 380V ± 10% 50Hz
输出电压(Max) Output Voltage (Max)	15KV	15KV	15KV
输出功率(Max) Output Opwer (Max)	20KW	30KW	60KW
工作频率 Operating Frequency	15-40KHz	15-40KHz	15-40KHz
外形尺寸(控制箱)(mm) Size of Control Cabinet (mm)	610x650x1700	610x650x1700	690x900x1900
变压器箱(mm) Size of Transformer Box (mm)	530x350x470	530x350x470x2	530x350x470x2
重量(控制箱+变压器箱)(Kg) Weight (Control Cabinet + Transformer Box)	175	175	320

## 南通三信塑胶装备科技股份有限公司

公司地址: 江苏省启东市台角工业区  
 网址: www.ntsaxin.com www.ntsaxin.cn  
 总机: 0513-83214154 传真: 0513-83214152  
 邮箱: ntsx@ntsaxin.com

## NANTONG SANXIN PLASTICS EQUIPMENT TECHNOLOGY CO.,LTD

Address:Taijiao Industrial Zone, Qidong City, Jiangsu Province, China  
 Website: www.ntsaxin.com www.ntsaxin.cn  
 Tel: 0086-513-83214154 Fax: 0086-513-83214152 Email: ntsx@ntsaxin.com